

COMPARISON

Bandit 2550 > CARLTON 6016

REDUCED MAINTENANCE COSTS

The cutter wheel on the 2550 is driven by a hydraulic motor mounted on the side. This hydraulic motor provides high torque while reducing the costs associated with a belt driven system. The Carlton cutter wheels are driven using a drive belt requiring additional maintenance. The cutter wheel drive on the 6016 is also engaged utilizing a jackshaft system, requiring additional maintenance on the jackshaft bearings and belt. The cutter wheel on the 2550 is simply engaged utilizing a hydraulic pump in turn activating the hydraulic motor and cutter wheel.

CONTROL OPTIONS

The 2550 is available with control valves mounted on the side of the machine or a wireless radio remote control. The 6016 is a newer machine, but from the specs listed it seems it is only available with a wireless radio remote control.



FEWER TEETH TO MAINTAIN

The 2550 comes equipped with 24 teeth (New Revolution wheel) and 18 teeth (Green wheel) compared to the Carlton's 36 teeth.

WEIGHT

The 2550 weighs approximately 800 pounds less compared to the 6016, allowing it to travel over softer ground conditions minimizing potential damage to the terrain.

A CHOICE OF ENGINE OPTIONS

The 2550 is offered with either a Kubota or Kohler 49 horsepower diesel engine along with a Kubota 49 gas engine. The Carlton 6016 is only offered with a Kubota gas engine. For those wanting more torque on their machine, we recommend the Kohler diesel engine as it provides 165 ft/lbs. of torque compared to the Kubota gas which has 88 ft/lbs. That equals 88% more torque! The Carlton 6016 is not offered with a diesel engine.



6750 MILLBROOK ROAD
REMUS, MICHIGAN 49340

1-800-952-0178

WWW.BANDITCHIPPERS.COM



All specifications, dimensions and options are subject to change without notice, and were current at the time of printing. Dimensions may vary, depending on options and engines selected. Bandit Industries, Inc. reserves the right to change designs, specifications and options without prior notice. © 2022 Bandit Industries, Inc. All Rights Reserved.

CALL YOUR LOCAL BANDIT SALES REPRESENTATIVE TO SCHEDULE A DEMONSTRATION TODAY!

MANUFACTURER:	BANDIT	CARLTON
Configuration:	2550	6016
DIMENSIONS		
Length:	120.5"	126"
Minimum Width:	35"	34.5"
Maximum Width:	54"	n/a
Height:	54"	50"
Weight:	2,280 lbs.	3,200 lbs.
ENGINE		
Horsepower Range:	49.6 HP Gas or Diesel	54.3 HP Kubota gas only
CUTTER WHEEL SYSTEM		
Operation:	Control valves or remote	Remote only
Cutterwheel Dimensions:	21" diameter x 1.25" thick	21" diameter x 1" thick
Engagement:	Hydrostatic	Jackshaft
Drive:	Hydraulic Motor	Belt
Number of Teeth:	18 or 24	36
Cutter Swing (inches):	53.5"	60" (arc)
Cutter Depth (inches):	15"	16"
Cutter Height (inches):	23.5"	25"
DRIVE SYSTEM		
Type:	Self-Propelled	Self-Propelled
Tires/Tracks:	Tires	Tires
TANKS		
Fuel Tank:	8.5 Gallon	10 Gallon
Hydraulic Tank:	8.5 Gallon	4 Gallon

BANDIT OFFERS A COMPLETE LINE OF TREE CARE EQUIPMENT:

- Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers
- The Beast® Horizontal Grinders • Track Carriers • Attachments