

COMPARISON

Bandit 2550 TRACK > RAYCO RG55T-R

BETTER VISIBILITY

The control valves mounted on the side of 2550 are positioned close to the cutter wheel allowing operator's to visually see better while grinding. The console on the Rayco RG55's is positioned further back and the engine is mounted on the boom making it difficult to see while grinding.

A CHOICE OF ENGINE OPTIONS

The 2550 is offered with either a Kubota or Kohler 49 horsepower diesel engine along with a Kubota 49 gas engine. The Rayco RG55's are only offered with a Kubota 54 gas engine. The Kubota gas engine will provide ok performance, but for max torque and productivity, we recommend the Kohler diesel engine as it provides 165 ft/lbs of torque compared to the Kubota gas which has 88 ft/lbs that equals 88% more torque! The Rayco RG55 is not offered with a diesel engine.

REDUCED MAINTENANCE COSTS

The cutter wheel on the 2550 is driven via a hydraulic motor mounted on the side. This hydraulic motor provides high torque while reducing the costs associated with a belt. The Rayco RG55 cutter wheels are driven using a drive belt requiring additional maintenance and downtime.



6750 MILLBROOK ROAD
REMUS, MICHIGAN 49340

1-800-952-0178

WWW.BANDITCHIPPERS.COM



All specifications, dimensions and options are subject to change without notice, and were current at the time of printing. Dimensions may vary depending on options and engines selected. Bandit Industries, Inc. reserves the right to change designs, specifications and options without prior notice. © 2021 Bandit Industries, Inc. All Rights Reserved.

CALL YOUR LOCAL BANDIT SALES REPRESENTATIVE TO SCHEDULE A DEMONSTRATION TODAY!

MANUFACTURER:	BANDIT	RACYO
Configuration:	2550 Track	RG55T-R
DIMENSIONS		
Length:	118"	144"
Minimum Width:	35"	35"
Maximum Width:	–	53"
Height:	54"	73"
Weight:	2,560 lbs.	3,360 lbs.
ENGINE		
Horsepower Range:	49 HP Kubota Gas/Diesel	54.3 HP Kubota Gas only
CUTTER WHEEL SYSTEM		
Cutterwheel Dimensions:	21" diameter x 1.25" thick	20" diameter x 1.5" thick
RPM:	1850 – 1900	–
Engagement:	Hydrostatic	Electric
Drive:	Hydraulic Motor	Belt
Number of Teeth:	18 or 24	24
Cutter Swing (inches):	53.5"	60"
Cutter Depth (inches):	15"	14"
Cutter Height (inches):	23.5"	24.5"
DRIVE SYSTEM		
Type:	Self-Propelled	Self-Propelled
Tires/Tracks:	Track Undercarriage	Track Undercarriage
Travel Speed:	–	–
TANKS		
Fuel Tank:	8.5 Gallon	8.5 Gallon
Hydraulic Tank:	8.5 Gallon	1.5 Gallon

BANDIT OFFERS A COMPLETE LINE OF TREE CARE EQUIPMENT:
 Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers
 The Beast® Horizontal Grinders • Track Carriers • Attachments