## **COMPARISON**

Bandit SG-40W > VERMEER SC292 / SC362 / SC382

## **CUTTER WHEEL OPTIONS**


The SG-40W features a 18" diameter x 1-1/2" thick cutter wheel, either as Bandit wheel with Greenteeth or a New Revolution wheel with hex teeth. Bandit offers these two cutter wheel options so customers can choose the best set-up that meets their needs.







**New Revolution Wheel** 









THE SG-40W'S CONTROL CONSOLE CAN BE PLACED IN THREE POSITIONS SO OPERATORS CAN GET THE BEST VIEW OF THE STUMP, DEPENDING ON CONDITIONS, **LOCATION AND STUMP SIZE.** 

The Vermeer controls located on one side of the machine reducing the flexibility during grinding.





6750 MILLBROOK ROAD **REMUS, MICHIGAN 49340** 1-800-952-0178 WWW.BANDITCHIPPERS.COM





## Bandit SG-40W > VERMEER SC292 / SC362 / SC382

MANUFACTURER:	BANDIT	VERMEER	VERMEER	VERMEER
Configuration:	SG-40W	SC292	SC362	SC382
		DIMENSIONS		
Length:	103"	110"	110"	118"
Minimum Width:	35"	35"	35"	35"
Maximum Width:	49"	49.8"	49.8"	50.1"
Height:	48"	52"	52"	53"
Weight:	1,750 lbs.	1,285 lbs.	1,320 lbs.	1,950 lbs.
		ENGINE		
Horsepower:	Kohler EFI 38 hp	Kohler 26.5 hp gas	Briggs 35 hp gas	Briggs 37 hp gas
		CUTTER WHEEL SYSTEM	I	
Cutterwheel Dimensions:	18" diameter x 1/2" thick	17" diameter x 1/2" thick	17" diameter x 1/2" thick	17" diameter x 1/2" thick
RPM:	2050	1,400	1,400	1,560
Engagement:	Electic	Electric	Electric	Electric
Drive:	Belt	V-belt	V-belt	V-belt
Number of Teeth:	8 or 24	16	16	20
Cutter Swing (inches):	47"	47"	47"	47"
Cutter Depth (inches):	12"	15"	15"	15"
Cutter Height (inches):	22"	24"	24"	24"
		DRIVE SYSTEM		
Туре:	Self-Propelled	Self-Propelled	Self-Propelled	Self-Propelled
Tires/Tracks:	Tire	Tire	Tire	Tire
Travel Speed:	2 MPH	66-133 f/m	66-133 f/m	66-133 f/m
		TANKS		
Fuel Tank:	7 Gallon	6 Gallon	6 Gallon	6 Gallon
Hydraulic Tank:	7 Gallon	4 Gallon	4 Gallon	6.5 Gallon