

# COMPARISON

*Intimidator™ 65XP > VERMEER BC700XL*

## THE 65XP FEATURES A WIDER ARRAY OF ENGINE OPTIONS THAN THE VERMEER 700XL.

The 700XL is only offered with a Kohler 25-horsepower gas engine, compared to the Model 65's 25 - 37 horsepower gas engine options. Customers looking at the Model 65XP can choose from Kohler or Vanguard engine options. The higher horsepower gas options provide more torque and power for more demanding chipping applications.

## THE THROAT OPENING ON THE 65XP IS 4" WIDER COMPARED TO THE 700XL

(6" x 12" compared to 6" x 8"). The larger opening means more production! Chainsaw work and labor are reduced.



## THE 65XP HAS A FEED RATE OF 80 FEET PER MINUTE COMPARED TO 49.4 FPM ON THE VERMEER 700XL.

## A 24.95 CID HYDRAULIC MOTOR IS FEATURED ON THE 65XP

while the Vermeer 700XL has a 14 CID. The larger feed motor on the 65xp generates 1,869.61 pounds of pulling power compared to the Vermeer's 1,114.65 pounds. The 65XP has approximately 40% more pulling power.



## THE 65XP HAS A LARGER INFEEED HOPPER OF 29" HIGH BY 42" WIDE

where the Vermeer 700XL has a 22" high by 41" wide hopper.



6750 MILLBROOK ROAD  
REMUS, MICHIGAN 49340

**1-800-952-0178**

[WWW.BANDITCHIPPERS.COM](http://WWW.BANDITCHIPPERS.COM)



All specifications, dimensions and options are subject to change without notice, and were current at the time of printing. Dimensions may vary, depending on options and engines selected. Bandit Industries, Inc. reserves the right to change designs, specifications and options without prior notice. © 2024 Bandit Industries, Inc. All Rights Reserved.

**CALL YOUR LOCAL BANDIT SALES REPRESENTATIVE TO SCHEDULE A DEMONSTRATION TODAY!**

MANUFACTURER:	BANDIT	VERMEER
Configuration:	Model 65XP	BC700XL
<b>MEASUREMENTS</b>		
Capacity:	6" diameter	6" diameter
Throat Opening:	12" wide x 6" tall	8" wide x 6" tall
Feed Rate (FPM):	80 FPM	49.4 FPM
<b>DIMENSIONS</b>		
Length (tray open):	12' 8"	11' 1"
Length (tray closed):	10' 8"	9' 3"
Width:	5' 7"	5' 11"
Height:	7' 6"	8' 6"
Weight:	2,000 lbs.	1,800 lbs.
<b>ENGINE</b>		
Horsepower Range:	25 – 37 HP	25 HP
<b>CHASSIS</b>		
Frame:	2" x 4"	3/16" Steel
Suspension:	2,200 or 3,500 lbs.	2,000 lbs.
Fenders:	Steel, 10-Gauge	Steel bolt-on
Hitch:	2" Ball	2" Ball
Axle/Undercarriage:	(1) 2,200 – 3,500 lb. Axle	2,000 lb. Axle
Tires/Tracks:	2	2
Tongue Jack:	2,000 lbs.	–
<b>FEED SYSTEM</b>		
Type:	Pivoting	Pivoting
Down Pressure Springs:	(2) 17" Adjustable Springs	–
Feed Wheels:	(1) Horizontal 10.625" diameter	(1) Horizontal 10" diameter
Number of Hydraulic Motors:	1	1
Displacement (CID):	24.95	14
Infeed Hopper Dimensions:	29" high x 42" wide	22" high x 41.2" wide
Bottom Clean Out Door:	n/a	n/a

MANUFACTURER:	BANDIT	VERMEER
Configuration:	Model 65XP	BC700XL
<b>CUTTING SYSTEM</b>		
Style:	Disc	Disc
Disc/Drum Dimensions:	26" diameter x .75" thick	23.9" diameter x 1.3" thick
RPM:	1,950	1,748
Knife Pockets:	2	2
Knives (thickness x width x length):	.5" thick x 4" wide x 7.25" long	.6" thick x 3.5" wide x 8" long
Chipper Shaft Diameter:	2"	–
Bearings:	2"	1.5"
<b>DISCHARGE</b>		
Swivel:	360°	360°
Deflector:	Manual	Manual
<b>TANKS</b>		
Fuel Tank Capacity:	7 Gallon	6 Gallon
Hydraulic Tank Capacity:	7 Gallon	6.8 Gallon

**BANDIT OFFERS A COMPLETE LINE OF TREE CARE EQUIPMENT:**  
 Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers  
 The Beast® Horizontal Grinders • Track Carriers • Attachments