COMPARISON

Bandit SG-40 > VERMEER SC30TX

HEAD-TO-HEAD. THE MODEL SG-40 WILL OUTPERFORM THE VERMEER.

The SG-40's belt driven cutter wheel provides a smooth aggressive cutting action and the belts are easily adjustable limiting downtime and maintenance costs. The Vermeer SC30TX features a hydraulic motor on the side of the machine to drive the cutter wheel. When a hydraulic motor was tested on the SG-40, it was determined a belt-driven solution was the best set-up for this size and horsepower machine.



The Vermeer controls are only at the back of the machine, meaning operators will have a limited view of the cutter wheel.



GREATER SWING ARC ALLOWS THE SG-40

to grind stumps reducing the amount of times the unit needs re-positioned. The SG-40 has a 44" wide swing arc compared to the SC30TX's 35 1/2" swing arc.





THE SG-40 IS OFFERED WITH A KOHLER 38 HP **EFI ENGINE PROVIDING** 58 FT/LBS OF TORQUE COMPARED TO THE SC30TX WITH A KOHLER 25 WITH 42 FT/LBS. THIS EQUALS **APPROXIMATELY 38% MORE** TORQUE!



6750 MILLBROOK ROAD **REMUS, MICHIGAN 49340** 1-800-952-0178 WWW.BANDITCHIPPERS.COM







MANUFACTURER:	BANDIT	VERMEER
Configuration:	SG-40	SC30TX
DIMENSIONS		
Length:	100.5"	94"
Minimum Width:	29"	35"
Maximum Width:	29"	35"
Height:	48"	49"
Weight:	1,500 lbs.	1,550 lbs.
ENGINE ENGINE		
Horsepower:	Kohler 38 hp EFI gas	Kohler 25 hp gas
CUTTER WHEEL SYSTEM		
Cutterwheel Dimensions:	18" diameter x 1/2" thick	16" diameter x 1/2" thick
RPM:	2,050	1,110
Engagement:	Electric	Electric
Drive:	Belt	Hydraulic Motor
Number of Teeth:	8 or 24	16
Cutter Swing (inches):	47"	35.5"
Cutter Depth (inches):	12"	12"
Cutter Height (inches):	22"	25"
DRIVE SYSTEM		
Туре:	Self-Propelled	Self-Propelled
Tires/Tracks:	Track	Track
Travel Speed:	2.5 MPH	3.2 MPH
TANKS		
Fuel Tank:	7 Gallon	6.8 Gallon
Hydraulic Tank:	7 Gallon	9 Gallon