

# COMPARISON

*Intimidator™ 12XC > Vermeer BC1000XL*

## EFFICIENT PULLING POWER

The 12XC features an aggressive single top feed wheel driven by a 32.3 CID hydraulic motor. The feed system on the 12XC generates approximately 44% more pulling power compared to the BC1000XL leading to greater operator productivity.

## SMOOTH FEEDING

The reversing auto feed system on the 12XC is programmed to work in conjunction with the engines RPM creating a smooth efficient chipping action. The Vermeer Smart Feed is designed to reverse the feed system on a frequent basis creating increased vibration, reduced feeding efficiency and chip quality.

## ENHANCED TORQUE

The drum on the 12XC rotates at 1,930 RPM for all engine configurations. The drum on the Vermeer BC1000XL turns at a rate ranging from 2,050 to 2,220 RPM. A slower turning drum will generate more torque resulting in a more powerful, yet smoother chipping action.

## DOWN PRESSURE

The 12XC generates abundant down pressure reducing the need to trim or re-position material. Side mounted springs can generate over 700 pounds of down pressure in the max setting and an optional hydraulic lift cylinder will provide an additional 2,200 pounds of down pressure. Vermeer advertises the BC1000XL has having 350 pounds of clamping force. When combining the springs and hydraulic lift cylinder on the 12XC, it will provide a substantial difference increasing chipping efficiency.



6750 MILLBROOK ROAD  
REMUS, MICHIGAN 49340

**1-800-952-0178**

[WWW.BANDITCHIPPERS.COM](http://WWW.BANDITCHIPPERS.COM)



All specifications, dimensions and options are subject to change without notice, and were current at the time of printing. Dimensions may vary depending on options and engines selected. Bandit Industries, Inc. reserves the right to change designs, specifications and options without prior notice. © 2024 Bandit Industries, Inc. All Rights Reserved.

**CALL YOUR LOCAL BANDIT SALES REPRESENTATIVE TO SCHEDULE A DEMONSTRATION TODAY!**

MANUFACTURER:	BANDIT	VERMEER
Configuration:	Intimidator™ 12XC	BC1000XL
MEASUREMENTS		
Capacity:	12" diameter	12" diameter
Throat Opening:	16 1/4" wide x 12 1/2" tall	17.5" wide x 12" tall
Feed Rate (FPM):	100 FPM	118 FPM
DIMENSIONS		
Length:	15' 11"	16' 6"
Width:	6' 7"	5' 6"
Height:	8' 4"	8' 5"
Weight:	4,400 - 4800 lbs.	4,680 - 5,000 lbs.
ENGINE		
Horsepower:	49 – 74 HP	49 – 74 HP
CHASSIS		
Frame:	1/4" x 4" Tubing	.25" x 7" Channel
Suspension:	6,000 lbs.	5,200 lbs.
Hitch:	2.5" Pintle	2.5" Pintle
Tires/Tracks:	(2) ST225/75R 15" Tires	(2) ST235/80R 16" Tires
Tongue Jack:	5,000 lbs.	5,000 lbs.
FEED SYSTEM		
Type:	Pivot Arm	Pivot Arm
Down Pressure Springs:	Springs / Optional lift cylinder (700 max with springs & 2,200 pounds with cylinder)	n/a, 350 lbs.
Feed Wheels:	(1) Horizontal	(1) Horizontal
Number of Hydraulic Motors:	1	1
Displacement (CID):	32.3	28.3
Infeed Hopper Dimensions:	30.75 high x 54" wide	32" high x 52" wide

MANUFACTURER:	BANDIT	VERMEER
Configuration:	Intimidator™ 12XC	BC1000XL
CUTTING SYSTEM		
Style:	Drum	Drum
Disc/Drum Dimensions:	20" diameter x 13 1/4" width	20" diameter x 20" width
RPM:	1,930	2,050 - 2,220
Knife Pockets:	2	2
Knives (thickness x width x length):	.625" x 5 1/2" x 6 1/8"	.625" thick x 4.5" wide x 9" long
Chipper Shaft Diameter:	3"	–
Bearings:	(2) 2.4375"	(2) 2.4375"
DISCHARGE		
Swivel:	360°	360°
Deflector:	Adjustable	Adjustable
TANKS		
Fuel Tank Capacity:	18 Gallon	20 - 25 Gallon
Hydraulic Tank Capacity:	8 Gallon	7 Gallon

**BANDIT OFFERS A COMPLETE LINE OF TREE CARE EQUIPMENT:**  
 Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers  
 Horizontal Grinders • Attachments