

COMPARISON

Bandit 12XC > Morbark BVR10

EFFICIENT PULLING POWER

The 12XC features an aggressive single top feed wheel driven by a 32.3 CID hydraulic motor. The feed system on the 12XC generates approximately 1,632 pounds of pulling power leading to greater operator productivity. Morbark does not list the hydraulic motor size or pulling power specs for the BVR10.

DOWN PRESSURE

The 12XC generates abundant down pressure reducing the need to trim or re-position material. Side mounted springs can generate over 700 pounds of down pressure in the max setting and an optional hydraulic lift cylinder will provide an additional 2,200 pounds of down pressure. Morbark doesn't list any down pressure specs, and does not have any hydraulic down pressure option for the BVR10.

DRUM ENGAGEMENT

The Bandit 12XC is available with an Auto or NACD spring loaded clutch to engage the drum. These clutches require little to no adjustments. The Morbark BVR10 engages the drum utilizing a centrifugal clutch. Centrifugal clutches are known for slipping and are prone to heat issues. If slipping occurs, there are no actions that can occur to prevent damage. With an actual clutch, the operator has complete control and can disengage immediately if there is an issue.

BANDIT CHIPPERS

are manufactured utilizing all steel components and solid welded construction for added durability and longevity. The BVR chippers are bolted together and utilize some plastic components. An all steel welded together machine will increase longevity and reduce unnecessary downtime.

MINIMAL ELECTRONIC COMPONENTS

The BVR line of Morbark chippers utilize more electronic components. Bandit chippers are engineered to use minimal electronic components for ease of service and less downtime.



6750 MILLBROOK ROAD
REMUS, MICHIGAN 49340

1-800-952-0178

WWW.BANDITCHIPPERS.COM



All specifications, dimensions and options are subject to change without notice, and were current at the time of printing. Dimensions may vary, depending on options and engines selected. Bandit Industries, Inc. reserves the right to change designs, specifications and options without prior notice. © 2024 Bandit Industries, Inc. All Rights Reserved.

CALL YOUR LOCAL BANDIT SALES REPRESENTATIVE TO SCHEDULE A DEMONSTRATION TODAY!

MANUFACTURER:	BANDIT	MORBARK
Configuration:	Intimidator™ 12XC	BVR10
MEASUREMENTS		
Capacity:	12" diameter	12" diameter
Throat Opening:	16 1/4" wide x 12 1/2" tall	14" high x 17 1/4" wide
Feed Rate (FPM):	100 FPM	–
DIMENSIONS		
Length:	15' 11"	13' 4"
Width:	6' 7"	7' 1"
Height:	8' 4"	8' 9"
Weight:	4,400 - 4800 lbs.	5,200 lbs.
ENGINE		
Horsepower:	49 – 74 HP	48 – 74 HP
CHASSIS		
Frame:	1/4" x 4" Tubing	5" Channel
Suspension:	6,000 lbs.	6,000 lbs.
Hitch:	2.5" Pintle	2 1/2" Pintle
Tires/Tracks:	(2) ST225/75R 15" Tires	235 / 80R 16"
Tongue Jack:	5,000 lbs.	–
FEED SYSTEM		
Type:	Pivot Arm	Pivot Arm
Down Pressure Springs:	Springs / Optional lift cylinder (700 max with springs & 2,200 pounds with cylinder)	Springs Only
Feed Wheels:	(1) Horizontal	(1) Horizontal
Number of Hydraulic Motors:	1	–
Displacement (CID):	32.3	–
Infeed Hopper Dimensions:	30.75 high x 54" wide	30" high x 60" wide

MANUFACTURER:	BANDIT	MORBARK
Configuration:	Intimidator™ 12XC	BVR10
CUTTING SYSTEM		
Style:	Drum	Drum
Disc/Drum Dimensions:	20" diameter x 13 1/4" width	18" diameter x 16.5" width
RPM:	1,930	–
Knife Pockets:	2	2
Knives (thickness x width x length):	.625" x 5 1/2" x 6 1/8"	–
Chipper Shaft Diameter:	3"	–
Bearings:	(2) 2.4375"	–
DISCHARGE		
Swivel:	360°	360°
Deflector:	Adjustable	Adjustable
TANKS		
Fuel Tank Capacity:	18 Gallon	17 Gallon
Hydraulic Tank Capacity:	8 Gallon	7 Gallon

BANDIT OFFERS A COMPLETE LINE OF TREE CARE EQUIPMENT:
 Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers
 Horizontal Grinders • Attachments